



# Material Safety Data Sheet

---

## 1. PRODUCT AND COMPANY IDENTIFICATION

---

**KATHON (TM) CF150 BIOCIDES**

Revision date: 10/22/2008

**Supplier** Rohm and Haas Company  
100 Independence Mall West  
Philadelphia, PA 19106-2399 United States of America

**For non-emergency information contact:** 215-592-3000

**Emergency telephone**  
Spill Emergency 215-592-3000  
Health Emergency 215-592-3000  
Chemtrec 800-424-9300

---

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

---

Component	CAS-No.	Concentration
5-Chloro-2-methyl-4-isothiazolin-3-one	26172-55-4	1.1 - 1.35%
2-Methyl-4-isothiazolin-3-one	2682-20-4	0.35 - 0.45%
Magnesium Chloride	7786-30-3	1.0 - 1.2%
Magnesium nitrate	10377-60-3	1.4 - 2.0%
Water	7732-18-5	95.0 - 96.0%

---

## 3. HAZARDS IDENTIFICATION

---

### Emergency Overview

### Appearance

**Form** liquid  
**Colour** Colorless to yellow  
**Odour** pungent

<b>Hazard Summary</b>	<b>DANGER!</b> CORROSIVE CAUSES SEVERE EYE/SKIN BURNS. MAY CAUSE SENSITIZATION BY SKIN CONTACT. IRRITATING TO RESPIRATORY SYSTEM.
-----------------------	---

**Potential Health Effects**

**Primary Routes of Entry:** Inhalation  
Eye contact  
Skin contact

**Eyes:** Material can cause the following:  
corrosion to eyes  
May cause permanent eye injury.

**Skin:** Material can cause the following:  
corrosion to the skin  
burns  
May cause sensitization of susceptible persons by skin contact.

**Ingestion:** May be harmful if swallowed.

**Inhalation:** Inhalation of vapor or mist can cause the following:  
irritation of nose, throat, and lungs

---

## 4. FIRST AID MEASURES

---

**Inhalation:** Move to fresh air. Give artificial respiration if breathing has stopped. If symptoms persist, call a physician.

**Skin contact:** IMMEDIATELY get under a safety shower. Remove contaminated clothing. Wash off with soap and water. Immediate medical attention is required. Wash contaminated clothing before re-use. Do not take clothing home to be laundered. Discard contaminated shoes, belts, and other articles made of leather.

**Eye contact:** Rinse immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

**Ingestion:** Drink 1 or 2 glasses of water. IMMEDIATELY see a physician. Never give anything by mouth to an unconscious person.

**Notes to physician:** MATERIAL IS CORROSIVE. It may not be advisable to induce vomiting. Possible mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock and convulsions maybe necessary.

---

## 5. FIRE-FIGHTING MEASURES

---

**Flash point** not applicable  
**Lower explosion limit** not applicable  
**Upper explosion limit** not applicable

**Suitable extinguishing media:** Use extinguishing media appropriate for surrounding fire.

**Specific hazards during fire fighting:** Combustion generates toxic fumes of the following: hydrogen chloride nitrogen oxides (NOx) sulfur oxides

**Special protective equipment for fire-fighters:** Wear self-contained breathing apparatus and protective suit.

**Further information:** Cool containers / tanks with water spray.  
Minimize exposure.  
Do not breathe fumes.  
Contain run-off.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### Personal precautions

Wear a NIOSH approved (or equivalent) respirator (with organic vapor/acid gas cartridge and a dust/mist filter) during spill clean-ups and deactivation of this material.

**MATERIAL IS CORROSIVE.** Protective clothing, including chemical splash goggles, nitrile or butyl rubber full length gloves, rubber apron, or clothing made of nitrile or butyl rubber, and rubber overshoes must be worn during spill clean-ups and deactivation of this material. If material comes in contact with the skin during clean-up operations, IMMEDIATELY remove all contaminated clothing and wash exposed skin areas with soap and water. See SECTION 4, First Aid Measures, for further information.

### Methods for cleaning up

**WARNING: KEEP SPILLS AND CLEAN-UP RESIDUALS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.** Adsorb the spill with spill pillows or inert solids such as clay or vermiculite, and transfer contaminated materials to suitable containers for disposal. Deactivate spill area with freshly prepared solution of 5% sodium bicarbonate and 5% sodium hypochlorite in water. Apply solution to the spill area at a ratio of 10 volumes deactivation solution per estimated volume of residual spill to deactivate any residual active ingredient. Let stand for 30 minutes. Flush the spill area with copious amounts of water to chemical sewer (if in accordance with local procedures, permits and regulations). DO NOT add deactivation solution to the waste pail to deactivate the adsorbed material. See Section 13, "Disposal Considerations", for information regarding the disposal of contained materials.

---

## 7. HANDLING AND STORAGE

---

### Handling

This material is corrosive. For personal protection see section 8. Do not handle material near food, feed or drinking water.

**Further information on storage conditions:** CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all MSDS and label warnings even after container is emptied. Expiration date based only on retention of >95% actives during storage at 20°C-25°C (68°F-77°F).

### Storage

**Storage conditions:** Keep in a well-ventilated place. The product as supplied may evolve gas (largely carbon dioxide) slowly. To prevent the buildup of pressure the product is packaged in specially vented containers, where necessary. Keep this product in the original container when not in use. Container must be stored and transported in an upright position to prevent spilling the contents through the vent, where fitted. Do not store this material in containers made of the following: steel Do not store this material near food, feed or drinking water.

**Storage temperature:**  $\geq 1$  °C ( $\geq 34$  °F)

**Storage temperature:**  $\leq 55$  °C ( $\leq 131$  °F)

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Exposure limit(s)

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value
5-Chloro-2-methyl-4-isothiazolin-3-one	Rohm and Haas	TWA	0.076 mg/m <sup>3</sup>
	Rohm and Haas	STEL	0.23 mg/m <sup>3</sup>

Component	Regulation	Type of listing	Value
2-Methyl-4-isothiazolin-3-one	Rohm and Haas	TWA	1.5 mg/m <sup>3</sup>
	Rohm and Haas	STEL	4.5 mg/m <sup>3</sup>

**Eye protection:** Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent). Eye protection worn must be compatible with respiratory protection system employed.

**Hand protection:** Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): butyl-rubber Nitrile rubber PVC gloves >1 mm thickness Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Rinse and remove gloves immediately after use. Wash hands with soap and water. NOTE: Material is a possible skin sensitizer.

**Skin and body protection:** Wear as appropriate: Chemical resistant apron complete suit protecting against chemicals

**Respiratory protection:** Typical use of this material does not result in workplace exposures that exceed the exposure limits listed in the Exposure Limit Information Section. For those special workplace conditions where the listed exposure limits are exceeded, a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. For concentrations up to 10 times the exposure limit, wear a properly fitted NIOSH approved (or equivalent) half-mask or full facepiece air purifying respirator equipped with organic vapor cartridges and N95 filters. If oil mist is present, use R95 or P95 filters. For those unlikely situations where exposure may greatly exceed the listed exposure limits (i.e. greater than 10-fold), or in any emergency situation, wear a properly fitted NIOSH approved (or equivalent) self-contained breathing apparatus in the pressure demand mode or a full facepiece airline respirator in the pressure demand mode with emergency escape provision. See SECTION 6, Accidental Release Measures, for respirator and protective clothing requirements for spill clean-up and decontamination of this material.

**Protective measures:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**Engineering measures:** Use local exhaust ventilation with a minimum capture velocity of 150 ft/min. (0.75 m/sec.) at the point of dust or mist evolution. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

---



---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**Appearance**

<b>Form</b>	liquid
<b>Colour</b>	Colorless to yellow
<b>Odour</b>	pungent
<b>pH</b>	2.0 - 4.0
<b>Boiling point/boiling range</b>	ca.100 °C ( 212.00 °F)
<b>Melting point/range</b>	-3.00 °C ( 26.60 °F)
<b>Flash point</b>	not applicable
<b>Lower explosion limit</b>	not applicable
<b>Upper explosion limit</b>	not applicable
<b>Relative vapour density</b>	ca.0.6
<b>Water solubility</b>	completely soluble
<b>Relative density</b>	1.02
<b>Viscosity, dynamic</b>	3.000 mPa.s at 25.00 °C (77.00 °F)
<b>Evaporation rate</b>	<1.00
<b>Percent volatility</b>	95 - 96 % Water

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---



---

## 10. STABILITY AND REACTIVITY

---

<b>Hazardous reactions</b>	Stable under recommended storage conditions.
<b>Materials to avoid</b>	Avoid contact with the following: Oxidizing agents Amines Reducing agents mercaptans
<b>Hazardous decomposition products</b>	nitrogen oxides (NOx), Sulphur oxides, hydrogen chloride,
<b>polymerization</b>	Product will not undergo polymerization.

---



---

## 11. TOXICOLOGICAL INFORMATION

---

<b>Acute oral toxicity</b>	LD50 rat female 3,310 mg/kg
	LD50 rat male > 5,000 mg/kg
<b>Acute inhalation toxicity</b>	LC50 rat 4 h 0.33 mg/l Active ingredient
<b>Acute dermal toxicity</b>	LD50 rabbit > 5,000 mg/kg
<b>Skin irritation</b>	rabbit Corrosive

<b>Eye irritation</b>	rabbit Corrosive
<b>Sensitisation</b>	guinea pig Causes sensitization.

**Carcinogenicity:**

Carcinogenicity: Non-carcinogenic in both a mouse dermal and rat oral carcinogenicity study. Active ingredient

**Toxicity to reproduction**

This product is not a reproductive hazard. Active ingredient

**Teratogenicity**

Did not show teratogenic effects in animal experiments. Active ingredient

**Mutagenicity**

Non-mutagenic Active ingredient

---

## 12. ECOLOGICAL INFORMATION

---

**Elimination information (persistence and degradability)****Biodegradability**

Biodegradation (aquatic metabolism): CAS # 26172-55-4 t 1/2 anaerobic = 4.8 hr, CAS # 26172-55-4 t 1/2 aerobic = 17.3 hr, CAS # 2682-20-4 t 1/2 aerobic = 9.1 hr

**Physico-chemical removability**

Activated Sludge Respiration Inhibition EC50: 4.5 mg/L ai

**Ecotoxicity effects****Toxicity to fish**

LC50 Oncorhynchus mykiss (rainbow trout) 96 h  
0.19 mg/l  
Active ingredient

**Toxicity to fish**

LC50 Bluegill sunfish 96 h  
0.28 mg/l  
Active ingredient

**Toxicity to algae**

EC50 Marine algae (Skeletonema costatum)  
0.003 mg/l  
Active ingredient

**Toxicity to algae**

EC50 Algae (Selenastrum capricornutum)  
0.018 mg/l  
Active ingredient

**Toxicity to aquatic invertebrates**

EC50 Daphnia magna 48 h  
0.16 mg/l  
Active ingredient

---

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal**

**Waste Classification:** When a decision is made to discard this material as supplied, it does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33. The toxicity characteristic (TC), however, has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.  
(See 40 CFR 268)

---

## 14. TRANSPORT INFORMATION

---

### DOT

<b>Proper shipping name</b>	Corrosive liquid, acidic, organic, n.o.s.(5-Chloro-2-methyl-4-isothiazolin-3-one)
<b>UN-Number</b>	UN 3265
<b>Class</b>	8
<b>Packing group</b>	II

### IMO/IMDG

<b>Proper shipping name</b>	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.(5-Chloro-2-methyl-4-isothiazolin-3-one)
<b>UN-Number</b>	UN 3265
<b>Class</b>	8
<b>Packing group</b>	II

*Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations*

---

## 15. REGULATORY INFORMATION

---

### Workplace Classification

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

This product is subject to regulation under the Canadian Pest Control Products Act (P.C.P. Act). Therefore, this product is excluded from the supplier labeling and material safety data sheet requirements as specified in Section 12 of the Hazardous Products Act.

**SARA TITLE III: Section 311/312 Categorizations (40CFR370):** Acute Health Hazard

### SARA TITLE III: Section 313 Information (40CFR372)

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

### CERCLA Information (40CFR302.4)

Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

**US. Toxic Substances Control Act (TSCA):** All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

---



---

**16. OTHER INFORMATION**


---

**Hazard Rating**

	<b>Health</b>	<b>Fire</b>	<b>Reactivity</b>
<b>HMIS</b>	3	0	0

**Legend**

ACGIH	American Conference of Governmental Industrial Hygienists
BAC	Butyl acetate
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit (STEL):
TLV	Threshold Limit Value
TWA	Time Weighted Average (TWA):
	Bar denotes a revision from prior MSDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Version: 1.3  
 Print Date: 10/25/2008  
 Layout 313025